

Description

Surface mounted simple shaped LED Downlight with exquisite appearance for modern commercial complexes, providing high quality, energy saving lighting solution.



SURFACE SERIES

MDLS COB 01 10/20/30 W

Installation

To be fitted in ceiling with the help of screws.

Salient Features

Energy saving upto 85% compared to standard halogen and incandescent lamp.

Long life upto 50000 Hrs.*

Easy to install, and can replace the traditional lamps directly.

High power factor of more than 0.9 and low THD.

High quality LED light source with high lumens, High CRI & standard CCT which make the light more soft.

Eco-friendly, no UV & IR Radiation, instant On & Off and high Lumen Output.



Application

Commercial Shops, Showrooms, Shopping Malls, Hotels, Offices, Houses etc.

Electrical Data

Cat. Ref.	Product Size (mm)	Nominal Voltage	Frequency Range	Power (Max.)	Beam Angle	Protection Grade	Luminous Flux	Shape
MDLS COB 01 10 W	79.5 × 130	AC, 240 V	50 Hz - 60 Hz	10 W	36	IP 20	660 LM	Round
MDLS COB 01 20 W	105 × 135	AC, 240 V	50 Hz - 60 Hz	20 W	24	IP 20	1535 LM	Round
MDLS COB 01 30 W	124 × 130	AC, 240 V	50 Hz - 60 Hz	30 W	36	IP 20	2250 LM	Round