

LED PANEL LIGHT

MESCAB

LED LIGHTING

Description

Recess mounted sleek and compact LED Panel light for modern offices providing high quality, energy saving lighting solutions.

Construction

Aluminium + PMMA

Installation

To be recessed in false ceiling with the help of spring loaded clamps.



RECESS SERIES

MPLR 02 3/6/9/12/15/18 W



Catalogue Reference	Wattage (W)	Dia (Ø)	Dimension (mm)		
			A	B	C
MPLR 02 3 W	3	85	75	20	85
MPLR 02 6 W	6	120	110	20	120
MPLR 02 9 W	9	146	135	20	146
MPLR 02 12 W	12	170	160	20	170
MPLR 02 15 W	15	200	185	20	200
MPLR 02 18 W	18	225	205	20	225

Electrical Data

Cat. Ref.	Product Size (mm)	Cut Out (mm)	Nominal Voltage	Frequency Range
MPLR 02 3 W	85 X 20	75	AC, 240 V	50 Hz - 60 Hz
MPLR 02 6 W	120 X 20	110	AC, 240 V	50 Hz - 60 Hz
MPLR 02 9 W	146 X 20	135	AC, 240 V	50 Hz - 60 Hz
MPLR 02 12 W	170 X 20	155	AC, 240 V	50 Hz - 60 Hz
MPLR 02 15 W	200 X 20	185	AC, 240 V	50 Hz - 60 Hz
MPLR 02 18 W	225 X 20	205	AC, 240 V	50 Hz - 60 Hz
MPLS 02 3 W	85 X 85 X 20	75 X 75	AC, 240 V	50 Hz - 60 Hz
MPLS 02 6 W	120 X 120 X 20	105 X 105	AC, 240 V	50 Hz - 60 Hz
MPLS 02 9 W	146 X 146 X 20	135 X 135	AC, 240 V	50 Hz - 60 Hz
MPLS 02 12 W	170 X 170 X 20	155 X 155	AC, 240 V	50 Hz - 60 Hz
MPLS 02 15 W	200 X 200 X 20	180 X 180	AC, 240 V	50 Hz - 60 Hz
MPLS 02 18 W	220 X 220 X 20	200 X 200	AC, 240 V	50 Hz - 60 Hz
MPLS 02 24 W	300 X 300 X 20	275 X 275	AC, 240 V	50 Hz - 60 Hz

LED PANEL LIGHT

MESCAB

LED LIGHTING

Salient Features

Energy saving upto 85% compared to standard halogen and incandescent lamp.

Durability – longer lifetime.

Fits in a small space over false ceiling.

High power factor and low THD.

Uniform, soft and bright diffused light output.

Eco-friendly, no UV & IR Radiation, instant On & Off, High CRI and Lumen Output.

Available in cool white, neutral white and warm white colours.


Application

Commercial, Residential, Show-rooms, Shopping Malls, Corridors, Lobby, Computer Centres, Banks, Hospitals, Conference Halls, Design Offices, Control Rooms, Laboratories etc.



RECESS SERIES

MPLS 02 3/6/9/12/15/18/24 W



Catalogue Reference	Wattage (W)	Dia (Ø)	Dimension (mm)		
			A	B	C
MPLS 02 3 W	3	85	75	20	85
MPLS 02 6 W	6	120	105	20	120
MPLS 02 9 W	9	146	135	20	146
MPLS 02 12 W	12	170	155	20	170
MPLS 02 15 W	15	200	180	20	200
MPLS 02 18 W	18	220	200	20	220
MPLS 02 24 W	24	300	275	20	300

Power (Watt)	LED Quantity	Beam Angle	Protection Grade	Luminous Flux	Shape
3 W	15	120°	IP 20	243 LM	Round
6 W	30	120°	IP 20	487 LM	Round
9 W	45	120°	IP 20	730 LM	Round
12 W	60	120°	IP 20	974 LM	Round
15 W	75	120°	IP 20	1218 LM	Round
18 W	90	120°	IP 20	1455 LM	Round
3 W	15	120°	IP 20	243 LM	Square
6 W	30	120°	IP 20	487 LM	Square
9 W	45	120°	IP 20	730 LM	Square
12 W	60	120°	IP 20	974 LM	Square
15 W	75	120°	IP 20	1218 LM	Square
18 W	90	120°	IP 20	1610 LM	Square
24 W	120	120°	IP 20	1948 LM	Square

* The above data is subject to change without prior notice due to continuous innovations and improvement in product.